



DC FAN LIFE EXPERIMENT REPORT

| | | | | | |
|---|------------|------------|------------|--|--|
| Available for these models with lower speed and same physical structure. All model may be followed by Rxx or Fxx series suffixes. This test report applies to AFB80x80x38mm series as the right table | AFB0824GHE | AFB0824EHE | AFB0824SHE | | |
| | AFB0812GHE | AFB0812EHE | AFB0812SHE | | |
| | | | | | |

Representative Test P/N :AFB0812GHE-F00

Equipment: 1.Oven: E24-W520 On/Off Cycles: Every 500 hours

☉ **L₁₀ Expectancy: 70,000 hours minimum @ fan rated voltage and the temperature of 40°C**

According to the equation for **Weibull distribution**, **MTTF ≐ 7×L10 = 490,000 hours**

And we rely on a zero failure Weibull test strategy and accelerated testing technique, to determine the total test time (t) for verifying the above life estimation by the equations,

$$t = 1.036 \times \text{MTTF} \times [(B_{r;c}) \div n]^{0.91} \div A_F, \text{ and } A_F = 2^{(T_s - T_u)/10}$$

where, (B_{r;c}) is Poisson distribution factor with the failure number of r equal to 0 and the decimal confidence level of c equal to 0.90(90%), and

| Stress/Elevated Temperature T _s (°C) (Actual Test Temperature) | Unstress Temperature T _u (°C) | Acceleration Factor A _F | Quantity of Test Devices n (pcs) | Poisson Distribution Factor B _{r;c} | Required test time with zero failure t (hours) | Actual test time with zero failure t (hours) | Verified MTTF 40 °C (hours) | Verified L ₁₀ 40 °C (hours) |
|--|--|------------------------------------|----------------------------------|--|--|--|-----------------------------|--|
| 70 | 40 | 8.00 | 56 | 2.303 | 3,478 | 3,478.0 | 490,031 | 70,004 |

Test Progress:

| Date for Test Beginning | Date for Test Termination (at least) | Current Test Status | | | Current Total Test Time (hours) |
|-------------------------|--------------------------------------|-------------------------------------|--|---|---------------------------------|
| 2006/3/17 10:30 AM | 2006/8/14 1:16 PM | <input type="checkbox"/> In process | <input type="checkbox"/> In process (exceed requested) | <input checked="" type="checkbox"/> Termination | 3478.0 |

Herewith , we could assume as right on the basis of above test result. Besides, if the actual test time exceed the required, it comes out that those fans' L10 expectancy and MTTF are greater than the warrant. (MTTF : means Mean Time To Failures, it should be used in a non-repairable system setting. Now we show the MTTF in our life report, that's because we will not repair the failed fans during life experiment. MTBF: means Mean Time Between failures, it should be used in a repairable system setting. Basically , MTBF is equal to MTTF , they use same formula to work out a life data.)

| Temperature for MTTF Estimation (°C) | Acceleration Factor A _F | Estimated MTTF (hours) | Estimated L ₁₀ (hours) |
|--------------------------------------|------------------------------------|------------------------|-----------------------------------|
| 25 | 22.63 | 1,386,017 | 198,002 |
| 30 | 16.00 | 980,062 | 140,009 |
| 40 | 8.00 | 490,031 | 70,004 |
| 50 | 4.00 | 245,015 | 35,002 |
| 60 | 2.00 | 122,508 | 17,501 |
| 70 | 1.00 | 61,254 | 8,751 |

Fan permission criteria for the measurement after test :

1. For current, the limit is less than spec.(max.).
2. For speed, the allowable decrease is less than 15%.
3. For noise, the limit is less than spec.(max.). + 3 dB

Test Result

- Accept**
 Reject

| QE File No. | Time-out for function test or others (hours) | Issued Date | Reported By | Approved By |
|-----------------------|--|--------------------------|-------------------|-------------------|
| WJQFML-2006045 | 125.00 | 2006/8/14 1:30 PM | YUHONG.SUN | ANGLER.LIU |



DC FAN FUNCTION TEST RECORD FOR LIFE EXPERIMENT

Available for these models with lower speed and same physical structure. All model may be followed by Rxx or Fxx series suffixes. This test report applies to AFB80x80x38mm series as the right table

| | | | |
|-------------------|-------------------|-------------------|--|
| AFB0824GHE | AFB0824EHE | AFB0824SHE | |
| AFB0812GHE | AFB0812EHE | AFB0812SHE | |
| | | | |

| Required Test Time (hrs) | Date for Test Beginning | Date for Test Termination | Sample Size (pcs): | Failure (pcs): | Current Total Test Time (hrs) |
|--------------------------|-------------------------|---------------------------|--------------------|----------------|-------------------------------|
| 3,478 | 2006/3/17 10:30 AM | 2006/8/14 1:16 PM | 56 | 0 | 3478.0 |

| | | | | |
|---|---------------------|-------------------------------------|--|---|
| Representative Test P/N :AFB0812GHE-F00 | Current Test Status | <input type="checkbox"/> In process | <input type="checkbox"/> In process (exceed requested) | <input checked="" type="checkbox"/> Termination |
|---|---------------------|-------------------------------------|--|---|

Equipment: 1.Oven: E24-W520 On/Off Cycles: Every 500 hours

Test Data Between Initial Test and Final Test

| Sample No. | Initial Test | Final Test | Deviation (%) | Initial Test | Final Test | Deviation (%) | Initial Test | Final Test | Deviation (%) |
|-----------------|-------------------|-------------------|---------------|-------------------|-------------------|---------------|--------------------|---------------------|---------------|
| | Current Spec. (A) | Current Spec. (A) | | Speed Spec. (RPM) | Speed Spec. (RPM) | | Noise Spec. (dB A) | Noise Check. (dB A) | |
| | 1.68Amax. | 1.68Amax. | | 6800±8% | 6800±8% | | 58.0max. | 58.0max. | |
| 1 | 1.28 | 1.19 | 6.8 | 6947 | 6920 | 0.4 | 54.7 | 55.7 | 1.8 |
| 2 | 1.28 | 1.16 | 9.2 | 7012 | 6649 | 5.2 | 54.3 | 55.4 | 2.0 |
| 3 | 1.24 | 1.14 | 8.2 | 6913 | 7273 | 5.2 | 54.3 | 55.6 | 2.4 |
| 4 | 1.30 | 1.19 | 8.7 | 7041 | 6747 | 4.2 | 54.6 | 55.1 | 0.9 |
| 5 | 1.26 | 1.17 | 7.5 | 6997 | 6944 | 0.8 | 54.7 | 55.4 | 1.3 |
| 6 | 1.24 | 1.11 | 10.3 | 6947 | 6631 | 4.5 | 55.2 | 55.8 | 1.1 |
| 7 | 1.34 | 1.15 | 14.2 | 7088 | 6639 | 6.3 | 54.8 | 55.4 | 1.1 |
| 8 | 1.34 | 1.25 | 6.9 | 7090 | 6844 | 3.5 | 54.7 | 56.0 | 2.4 |
| 9 | 1.31 | 1.24 | 5.4 | 7063 | 6769 | 4.2 | 55.0 | 55.5 | 0.9 |
| 10 | 1.31 | 1.17 | 10.7 | 7100 | 6711 | 5.5 | 55.6 | 55.3 | 0.5 |
| 11 | 1.32 | 1.16 | 12.5 | 7055 | 6863 | 2.7 | 54.5 | 55.1 | 1.1 |
| 12 | 1.27 | 1.15 | 9.3 | 6992 | 6944 | 0.7 | 55.0 | 56.5 | 2.7 |
| 13 | 1.26 | 1.11 | 11.7 | 7037 | 6716 | 4.6 | 55.4 | 55.9 | 0.9 |
| 14 | 1.23 | 1.16 | 5.6 | 6954 | 7147 | 2.8 | 54.6 | 55.1 | 0.9 |
| 15 | 1.30 | 1.15 | 11.5 | 6991 | 6863 | 1.8 | 54.7 | 56.6 | 3.5 |
| 16 | 1.24 | 1.18 | 5.1 | 6968 | 6622 | 5.0 | 54.9 | 55.4 | 0.9 |
| 17 | 1.29 | 1.16 | 9.8 | 6964 | 7315 | 5.0 | 54.9 | 55.6 | 1.3 |
| 18 | 1.23 | 1.13 | 8.5 | 6923 | 6716 | 3.0 | 55.3 | 54.9 | 0.7 |
| 19 | 1.29 | 1.18 | 8.7 | 7009 | 6702 | 4.4 | 56.1 | 56.2 | 0.2 |
| 20 | 1.32 | 1.16 | 11.8 | 7090 | 6622 | 6.6 | 54.9 | 55.3 | 0.7 |
| 21 | 1.28 | 1.15 | 10.5 | 7003 | 6614 | 5.6 | 56.0 | 56.1 | 0.2 |
| 22 | 1.28 | 1.16 | 9.5 | 6992 | 6510 | 6.9 | 56.0 | 55.5 | 0.9 |
| 23 | 1.33 | 1.26 | 5.2 | 7060 | 6595 | 6.6 | 55.7 | 56.1 | 0.7 |
| 24 | 1.33 | 1.17 | 11.7 | 7088 | 6604 | 6.8 | 55.9 | 55.9 | 0.0 |
| 25 | 1.30 | 1.13 | 13.5 | 7002 | 6561 | 6.3 | 55.7 | 55.7 | 0.0 |
| 26 | 1.37 | 1.11 | 18.8 | 6682 | 6863 | 2.7 | 55.7 | 56.0 | 0.5 |
| 27 | 1.27 | 1.19 | 6.7 | 6975 | 6555 | 6.0 | 55.4 | 55.4 | 0.0 |
| 28 | 1.30 | 1.16 | 11.0 | 6997 | 6635 | 5.2 | 55.6 | 55.1 | 0.9 |
| 29 | 1.30 | 1.20 | 8.0 | 7078 | 6659 | 5.9 | 55.7 | 55.4 | 0.5 |
| 30 | 1.24 | 1.12 | 10.0 | 6968 | 6644 | 4.6 | 55.8 | 55.1 | 1.3 |
| 31 | 1.24 | 1.13 | 8.9 | 6934 | 6433 | 7.2 | 55.4 | 55.9 | 0.9 |
| 32 | 1.30 | 1.16 | 11.0 | 6951 | 6455 | 7.1 | 56.0 | 56.0 | 0.0 |
| 33 | 1.31 | 1.20 | 8.5 | 7058 | 6852 | 2.9 | 56.4 | 55.4 | 1.8 |
| 34 | 1.35 | 1.17 | 13.3 | 7048 | 6762 | 4.1 | 55.8 | 56.7 | 1.6 |
| 35 | 1.28 | 1.18 | 7.7 | 7066 | 6697 | 5.2 | 55.5 | 55.0 | 0.9 |
| Mean (X-Stdard) | 1.289 | 1.165 | - | 7002.4 | 6741.6 | - | 55.28 | 55.63 | - |
| | 0.036 | 0.036 | - | 77.610 | 205.326 | - | 0.570 | 0.461 | - |

| QE File No. | Time-out for function test or others (hours) | Issued Date | Reported By | Approved By |
|----------------|--|-------------------|-------------|-------------|
| WJQFML-2006045 | 125.00 | 2006/8/14 1:30 PM | YUHONG.SUN | ANGLER.LIU |



DC FAN FUNCTION TEST RECORD FOR LIFE EXPERIMENT

Available for these models with lower speed and same physical structure. All model may be followed by Rxx or Fxx series suffixes. This test report applies to AFB80x80x38mm series as the right table

| | | | |
|-------------------|-------------------|-------------------|--|
| AFB0824GHE | AFB0824EHE | AFB0824SHE | |
| AFB0812GHE | AFB0812EHE | AFB0812SHE | |
| | | | |

| Required Test Time (hrs) | Date for Test Beginning | Date for Test Termination | Sample Size (pcs): | Failure (pcs): | Current Total Test Time (hrs) |
|--------------------------|-------------------------|---------------------------|--------------------|----------------|-------------------------------|
| 3,478 | 2006/3/17 10:30 AM | 2006/8/14 1:16 PM | 56 | 0 | 3478.0 |

| | | | | |
|---|----------------------------|-------------------------------------|--|---|
| Representative Test P/N :AFB0812GHE-F00 | Current Test Status | <input type="checkbox"/> In process | <input type="checkbox"/> In process (exceed requested) | <input checked="" type="checkbox"/> Termination |
|---|----------------------------|-------------------------------------|--|---|

Equipment: 1.Oven: E24-W520 On/Off Cycles: Every 500 hours

Test Data Between Initial Test and Final Test

| Sample No. | Initial Test Current Spec. (A) | Final Test Current Spec. (A) | Deviation (%) | Initial Test Speed Spec. (RPM) | Final Test Speed Spec. (RPM) | Deviation (%) | Initial Test Noise Spec. (dB A) | Final Test Noise Check. (dB A) | Deviation (%) |
|-----------------|--------------------------------|------------------------------|---------------|--------------------------------|------------------------------|---------------|---------------------------------|--------------------------------|---------------|
| | (A) | (A) | | (RPM) | (RPM) | | (dB A) | (dB A) | |
| | 1.68Amax. | 1.68Amax. | | 6800±8% | 6800±8% | | 58.0max. | 58.0max. | |
| 36 | 1.27 | 1.17 | 8.2 | 6985 | 6485 | 7.2 | 55.2 | 56.0 | 1.4 |
| 37 | 1.29 | 1.14 | 11.3 | 7063 | 6570 | 7.0 | 55.8 | 56.1 | 0.5 |
| 38 | 1.31 | 1.20 | 8.7 | 7065 | 6550 | 7.3 | 55.4 | 55.4 | 0.0 |
| 39 | 1.25 | 1.16 | 6.9 | 6966 | 6587 | 5.4 | 55.1 | 55.2 | 0.2 |
| 40 | 1.29 | 1.20 | 6.7 | 6869 | 6424 | 6.5 | 55.0 | 55.7 | 1.3 |
| 41 | 1.30 | 1.16 | 10.7 | 7024 | 6733 | 4.1 | 55.5 | 55.6 | 0.2 |
| 42 | 1.25 | 1.17 | 6.5 | 6994 | 6514 | 6.9 | 55.2 | 56.6 | 2.5 |
| 43 | 1.34 | 1.21 | 9.9 | 6800 | 7341 | 8.0 | 55.8 | 56.3 | 0.9 |
| 44 | 1.29 | 1.16 | 10.2 | 7042 | 6988 | 0.8 | 55.3 | 55.7 | 0.7 |
| 45 | 1.29 | 1.17 | 9.7 | 7031 | 6514 | 7.4 | 55.5 | 55.4 | 0.2 |
| 46 | 1.23 | 1.14 | 7.6 | 6933 | 6566 | 5.3 | 54.9 | 55.6 | 1.3 |
| 47 | 1.30 | 1.18 | 9.5 | 6991 | 6513 | 6.8 | 55.3 | 55.8 | 0.9 |
| 48 | 1.28 | 1.19 | 7.0 | 7000 | 6578 | 6.0 | 56.2 | 55.3 | 1.6 |
| 49 | 1.31 | 1.16 | 11.4 | 7022 | 6733 | 4.1 | 56.0 | 55.4 | 1.1 |
| 50 | 1.32 | 1.16 | 12.2 | 7043 | 6671 | 5.3 | 56.1 | 55.2 | 1.6 |
| 51 | 1.23 | 1.13 | 8.5 | 6960 | 6639 | 4.6 | 56.7 | 55.7 | 1.8 |
| 52 | 1.33 | 1.17 | 12.1 | 7018 | 6545 | 6.7 | 56.2 | 55.5 | 1.2 |
| 53 | 1.24 | 1.17 | 6.0 | 6950 | 7337 | 5.6 | 55.6 | 54.7 | 1.6 |
| 54 | 1.30 | 1.16 | 10.5 | 6964 | 6607 | 5.1 | 55.8 | 55.1 | 1.3 |
| 55 | 1.31 | 1.17 | 11.0 | 7107 | 6631 | 6.7 | 56.3 | 56.4 | 0.2 |
| 56 | 1.30 | 1.18 | 9.0 | 7021 | 6521 | 7.1 | 56.1 | 55.2 | 1.6 |
| Mean (X-Stdard) | 1.287 | 1.168 | - | 6992.8 | 6668.9 | - | 55.67 | 55.61 | - |
| | 0.031 | 0.020 | - | 68.369 | 251.702 | - | 0.488 | 0.467 | - |

| QE File No. | Time-out for function test or others (hours) | Issued Date | Reported By | Approved By |
|-----------------------|--|--------------------------|-------------------|-------------------|
| WJQFML-2006045 | 125.00 | 2006/8/14 1:30 PM | YUHONG.SUN | ANGLER.LIU |